
domain2idna Documentation

Nissar Chababy (@funilrys)

Oct 10, 2022

Content

1	Requirements	3
1.1	Python 3.6.8+ && Python < 4	3
1.2	colorama	3
2	Get and install domain2idna	5
2.1	Using pip	5
2.2	Using conda	6
2.3	Pure Python method	6
3	First steps	7
4	Usage	9
4.1	As a Python module	9
4.2	From a terminal	10
5	Code documentation	11
5.1	Helpers	12
5.2	Converter	13
6	Issues	15
7	Indices and tables	17
	Python Module Index	19
	Index	21

Here is the list of requirements:

- Python 3.6.2+ && Python < 4
- `colorama`

1.1 Python 3.6.8+ && Python < 4

The specification `3.6.8+` is because we test `domain2idna` (daily) in all version from `3.6.8`. Otherwise, more semantically, `domain2idna` is written for all Python 3.6+ version.

1.2 `colorama`

As we want to add some coloration, we choose `colorama` for the job as it offers a portable awesome solution.

Get and install domain2idna

2.1 Using pip

Choose your repository, install and enjoy domain2idna!

2.1.1 From PyPi

```
$ pip3 install --user domain2idna
```

Note: We recommend the `--user` flag which installs the required dependencies at the user level. More information about it can be found on [pip documentation](#).

Warning: We do not recommend the `--user` flag when using domain2idna into containers like - for example - Travis CI.

2.1.2 From GitHub

```
$ pip3 install --user git+https://github.com/PyFunceble/domain2idna.git@master  
→#egg=domain2idna
```

Note: We recommend the `--user` flag which installs the required dependencies at the user level. More information about it can be found on [pip documentation](#).

Warning: We do not recommend the `--user` flag when using `domain2idna` into containers like - for example - Travis CI.

2.2 Using `conda`

```
$ conda install -c pyfunceble domain2idna
```

2.3 Pure Python method

Execute the following and enjoy `domain2idna`!

We clone the repository.

```
$ git clone https://github.com/PyFunceble/domain2idna.git
```

We move to the cloned directory.

```
$ cd domain2idna
```

We test the package before installing.

```
$ python3 setup.py test
```

We install `domain2idna`.

```
$ python3 setup.py install --user
```

Note: We recommend the `--user` flag which installs the required dependencies at the user level. More information about it can be found on [pip documentation](#).

Warning: We do not recommend the `--user` flag when using `domain2idna` into containers like - for example - Travis CI.

CHAPTER 3

First steps

Make sure that you can run the following without any issue and enjoy domain2idna!!

```
$ domain2idna --version
```


4.1 As a Python module

Here's an example which show us how domain2idna can be used a python module.

```
#!/usr/bin/env python3

"""
This module uses domains2idna to convert a given domain.

Author:
    Nissar Chababy, @funilrys, contactTATAfunilrystODTODcom

Contributors:
    Let's contribute to this example!!

Repository:
    https://github.com/PyFunceble/domain2idna
"""
from domain2idna import domain2idna

DOMAINS = [
    "bittr .com", "bllogram.com", "coinbse.com", "cryptopi.com", "cyptopia.com"
]

# The following return the result of the whole list.
print("UTF-8 domains: %s" % DOMAINS)
print("Converted domains: %s" % domain2idna(DOMAINS))

# The following return the result of only one element.
print("UTF-8 domain: %s" % DOMAINS[0])
print("Converted domain: %s" % domain2idna(DOMAINS[0]))
```

4.2 From a terminal

Here is the list of available command when calling domain2idna from a terminal.

```
usage: domain2idna [-h] [-s SUBJECT [SUBJECT ...]] [-e ENCODING] [-f FILE] [-o OUTPUT] [-v]

domain2idna - The tool to convert a domain or a file with a list of domain to the famous IDNA format.

optional arguments:
  -h, --help                show this help message and exit
  -s SUBJECT [SUBJECT ...], --subject SUBJECT [SUBJECT ...]
                           Sets the subjects to convert.
  -e ENCODING, --encoding ENCODING
                           Sets the encoding to use.
  -f FILE, --file FILE      Sets the file to read to get the domain(s) to convert.
  -o OUTPUT, --output OUTPUT
                           Sets the file where we write the converted domain(s).
  -v, --version              show program's version number and exit

Crafted with  by Nissar Chababy (Funilrys)
```

Code documentation

domain2idna - The tool to convert a domain or a file with a list of domain to the famous IDNA format.

Author: Nissar Chababy, @funilrys, contactTATAfunilrysTODTODcom

Contributors: Let's contribute to domains2idna!!

Project link: <https://github.com/PyFuncible/domain2idna>

Project documentation: <http://domain2idna.readthedocs.io>

License:

```
MIT License
```

```
Copyright (c) 2019, 2020, 2021, 2022 PyFuncible  
Copyright (c) 2018, 2019, 2020, 2021, 2022 Nissar Chababy
```

```
Permission is hereby granted, free of charge, to any person obtaining a copy  
of this software and associated documentation files (the "Software"), to deal  
in the Software without restriction, including without limitation the rights  
to use, copy, modify, merge, publish, distribute, sublicense, and/or sell  
copies of the Software, and to permit persons to whom the Software is  
furnished to do so, subject to the following conditions:
```

```
The above copyright notice and this permission notice shall be included in all  
copies or substantial portions of the Software.
```

```
THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR  
IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY,  
FITNESS FOR A PARTICULAR PURPOSE AND NON-INFRINGEMENT. IN NO EVENT SHALL THE  
AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER  
LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM,  
OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE  
SOFTWARE.
```

```
domain2idna.domain2idna (subject, encoding='utf-8')  
    Process the conversion of the given subject.
```

Parameters

- **subject** (*str*, *list*) – The subject to convert.
- **encoding** (*str*) – The encoding to provide.

Return type list, str

`domain2idna.get (domain_to_convert)`

This function is a passerelle between the front and the backend of this module.

Parameters **domain_to_convert** (*str*) – The domain to convert.

Returns

str: if a string is given.

list: if a list is given.

Return type str, list

Deprecated since version 1.10.0: Use `domain2idna ()` instead.

5.1 Helpers

5.1.1 Problematic

How can we write, read and delete a file without having to write everytime the same thing?

5.1.2 Code documentation

`File()`

class `domain2idna.helpers.File (filename)`

File treatment/manipulations.

Parameters **filename** (*str*) – A path to the file to manipulate.

delete ()

Deletes a given file path.

Warning: We handle the case that the file does not exist.

read (encoding=None)

Reads a given file path and return its content.

Parameters **encoding** (*str*) – The encoding to use when opening the file.

Return type str

write (data_to_write)

Writes or appends data into the given file path.

Parameters **data_to_write** (*str*) – The data to write.

5.2 Converter

5.2.1 Code documentation

class `domain2idna.converter.Converter` (*subject*, *original_encoding*='utf-8')

Provides a base for every core logic we add.

Parameters

- **subject** (*str*, *list*) – The subject to convert.
- **original_encoding** (*str*) – The encoding to provide as output.

convert_to_idna (*subject*, *original_encoding*='utf-8')

Converts the given subject to IDNA.

Parameters **subject** (*str*) – The subject to convert.

Return type `str`

get_converted ()

Provides the converted data.

CHAPTER 6

Issues

Have or found an issue with `domain2idna`? Please follow one of the following.

- Fill a [new issue](#).
- Send a email to contactTATATAfunilrysTODTOTODcom.

CHAPTER 7

Indices and tables

- `genindex`
- `modindex`
- `search`

d

`domain2idna`, 11

C

`convert_to_idna()` (*domain2idna.converter.Converter* method),
13

`Converter` (*class in domain2idna.converter*), 13

D

`delete()` (*domain2idna.helpers.File* method), 12

`domain2idna` (*module*), 11

`domain2idna()` (*in module domain2idna*), 11

F

`File` (*class in domain2idna.helpers*), 12

G

`get()` (*in module domain2idna*), 12

`get_converted()` (*domain2idna.converter.Converter* method),
13

R

`read()` (*domain2idna.helpers.File* method), 12

W

`write()` (*domain2idna.helpers.File* method), 12